



# G-STAR COMMUNICATIONS LTD.

Web: [www.gstarcom.com](http://www.gstarcom.com) E-mail: [info@gstarcom.com](mailto:info@gstarcom.com)



## GU-721-26

### UNIVERSAL SINGLE LNBF

#### LO 11.30 GHz KU Band LNB

<b>Input Frequency Range</b>	12.20 ~ 12.75 GHz
<b>Reflector Type</b>	Offset
<b>Cross Polarization Isolation</b>	20 dB (Min.) / 25 dB (Typical)
<b>Noise Figure</b>	0.6 dB (Typical)
<b>Conversion Gain</b>	50 dB (Min.) / 55 dB (Max.)
<b>Gain Flatness</b>	±0.5 dB / 24 MHz
<b>Output Frequency Range</b>	900 ~ 1450 MHz
<b>L.O. Frequency</b>	11.30 GHz
<b>L.O. Phase Noise</b>	-55 dBc / Hz (@ 1 KHz) -80 dBc / Hz (@ 10 KHz) -100 dBc / Hz (@ 100 KHz)
<b>L.O Frequency Stability</b>	1. ±1 MHz (Room Temperature) 2. ±3 MHz (-40°C to +60°C)
<b>Output Connector</b>	75 Ω F Type Female
<b>Operating Voltage</b>	(1) 11.5 ~ 14.0 V → Vertical Polarization (2) 16.0 ~ 19.0 V → Horizontal Polarization
<b>Operating Temperature</b>	-40°C to +60°C